


Signature Hinged Door TB (100mm)

Installation Details

BRICK VENEER CONSTRUCTION - HEAD & JAMB



NOTE:
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A $\phi 2.2$ mm STEEL NAIL MINIMUM.

PRODUCT NO: TBSHD_100

DRAWING NO: TB-SIG-HD-02-01


DRAWN: DJH

DATE: 04/07/14

ISSUE: A

SCALE: 1 : 3

BRICK VENEER CONSTRUCTION - SILL & JAMB



NOTE:
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A \varnothing 2.2mm STEEL NAIL MINIMUM.

PRODUCT NO: TBSHD_100

DRAWING NO: TB-SIG-HD-02-02


DRAWN: DJH

DATE: 04/07/14

ISSUE: A

SCALE: 1 : 3

CLADDING CONSTRUCTION - HEAD & JAMB



NOTE:
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A $\varnothing 2.2\text{mm}$ STEEL NAIL MINIMUM.

PRODUCT NO: TBSHD_100

DRAWING NO: TB-SIG-HD-02-03


DRAWN: DJH

DATE: 04/07/14

ISSUE: A

SCALE: 1 : 3

CLADDING CONSTRUCTION - SILL & JAMB



NOTE:
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A ϕ 2.2mm STEEL NAIL MINIMUM.

PRODUCT NO: TBSHD_100

DRAWING NO: TB-SIG-HD-02-04


DRAWN: DJH

DATE: 04/07/14

ISSUE: A

SCALE: 1 : 3

CAVITY BRICK CONSTRUCTION - HEAD & JAMB DETAIL



NOTE:
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A ϕ 2.2mm STEEL NAIL MINIMUM.

PRODUCT NO: TBSHD_100

DRAWING NO: TB-SIG-HD-02-05


DRAWN: DJH

DATE: 04/07/14

ISSUE: A

SCALE: 1 : 3

CAVITY BRICK CONSTRUCTION - SILL & JAMB DETAIL



NOTE:
FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A $\phi 2.2$ mm STEEL NAIL MINIMUM.

PRODUCT NO: TBSHD_100

DRAWING NO: TB-SIG-HDV-02-06

DRAWN: DJH

DATE: 04/07/14

ISSUE: A


SCALE: 1 : 3



SUNCOAST
WINDOWS

Quality . Style . Innovation

BLOCKWORK CONSTRUCTION - HEAD & JAMB DETAIL



NOTE:

SURFACE OF BLOCKS TO WINDOW OPENING MUST BE TANKED WITH A SUITABLE SEALER TO PREVENT INGRESS OF MOISTURE. ENSURE SURFACES TO BE SEALED ARE SOUND, CLEAN, DRY AND FREE FROM ANY CONTAMINANTS BEFORE SEALING.

FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A ϕ 2.2mm STEEL NAIL MINIMUM.

PRODUCT NO: TBSHD_100

DRAWING NO: TB-SIG-HD-02-07

DRAWN: DJH

DATE: 04/07/14

ISSUE: A


SCALE: 1 : 3



SUNCOAST
WINDOWS

Quality . Style . Innovation

BLOCKWORK CONSTRUCTION - SILL & JAMB DETAIL



NOTE:
SURFACE OF BLOCKS TO WINDOW OPENING MUST BE TANKED WITH A SUITABLE SEALER TO PREVENT INGRESS OF MOISTURE. ENSURE SURFACES TO BE SEALED ARE SOUND, CLEAN, DRY AND FREE FROM ANY CONTAMINANTS BEFORE SEALING.

FOR SITE CLASSIFICATIONS OF UP TO AND INCLUDING 'N6' OR SIMILAR, FIXINGS ARE TO BE AT 450mm CENTRE MAXIMUM, FOR SITUATIONS IN EXCESS OF THIS THE FIXINGS ARE TO BE AT 300mm CENTRES MAXIMUM. FIXING SIZE TO BE EQUIVALENT TO A ϕ 2.2mm STEEL NAIL MINIMUM.

PRODUCT NO: TBSHD_100

DRAWING NO: TB-SIG-HD-02-08

DRAWN: DJH

DATE: 20/11/14


ISSUE: A

SCALE: 1 : 3



SUNCOAST
WINDOWS
Quality . Style . Innovation

CONCRETE CONSTRUCTION - HEAD & JAMB DETAIL



NOTE:

SURFACE OF CONCRETE TO WINDOW OPENING MUST BE TANKED WITH A SUITABLE SEALER TO PREVENT INGRESS OF MOISTURE. ENSURE SURFACES TO BE SEALED ARE SOUND, CLEAN, DRY AND FREE FROM ANY CONTAMINANTS BEFORE SEALING.

FIXING TYPES & CENTRES TO BE PROJECT SPECIFIC, REFER TO SPECIFICATION AND/OR ENGINEER.

PRODUCT NO: TBSHD_100

DRAWING NO: TB-SIG-HD-02-09

DRAWN: DJH

DATE: 04/07/14

ISSUE: A


SCALE: 1 : 3



SUNCOAST
WINDOWS

Quality . Style . Innovation

CONCRETE CONSTRUCTION - SILL & JAMB DETAIL



NOTE:

SURFACE OF CONCRETE TO WINDOW OPENING MUST BE TANKED WITH A SUITABLE SEALER TO PREVENT INGRESS OF MOISTURE. ENSURE SURFACES TO BE SEALED ARE SOUND, CLEAN, DRY AND FREE FROM ANY CONTAMINANTS BEFORE SEALING.

FIXING TYPES & CENTRES TO BE PROJECT SPECIFIC, REFER TO SPECIFICATION AND/OR ENGINEER.

PRODUCT NO: TBSHD_100

DRAWING NO: TB-SIG-HD-02-10

DRAWN: DJH

DATE: 04/07/14

ISSUE: A


SCALE: 1 : 3




SUNCOAST
WINDOWS

Quality . Style . Innovation

SUBSILL DAM ANGLE INSTALLATION



1. INSTALL SUBSILL INTO OPENING WITH DAM ANGLE FITTED. PACK SUBSILL LEVEL THEN FIX TO STRUCTURE. SEAL SUBSILL ENDS TO STRUCTURE.




2. APPLY SEALANT TO VERTICAL FACE OF DAM ANGLE AND ALSO TO THE FLOOR OF THE SUBSILL. POSITION DAM ANGLE AGAINST STRUCTURE. SEAL ALL JOINTS BETWEEN ANGLE AND SUBSILL. SEAL ALL JOINTS BETWEEN ANGLE AND SUBSILL. SEAL OVER FIXINGS AND UNDER SUB SILL TO STRUCTURE.

PRODUCT NO: TBSHD_100
DRAWING NO: TB-SIG-HD-02-11
DRAWN: DJH

DATE: 04/07/14
ISSUE: A
SCALE: 1 : 4

SUBSILL DAM ANGLE INSTALLATION WITH THE FIXING & TRIM ANGLES



PRODUCT NO: TBSHD_100

DRAWING NO: TB-SIG-HD-02-12

DRAWN: DJH

DATE: 04/07/14

ISSUE: A

SCALE: 1 : 1.5



**SUNCOAST
WINDOWS**

Quality . Style . Innovation